



AN INTERNATIONAL PAPER INDUSTRY STANDARD

Ultra™

High-performance braided carrier rope designed for demanding paper machine applications.

1

Engineered Coating

Proprietary Ultra coating delivers outstanding abrasion resistance.

2

Stable performance

Heat-set construction provides stability and durability.

3

Easy identification

Range of colors helps identify inside, center and outside rope positions.

4

Splicing support

Designed for William Kenyon® basket-fid splicing method.

MANUFACTURING SPECIFICATIONS

Ultra™ / Ultra KM - Standard construction

Pre-stretched coated filament carrier rope for demanding paper machine applications.

STYLE	DIAMETER	APPROX. BREAK STRENGTH	STANDARD STOCK LENGTH
Ultra Filament Coated	3/8 in	4,000 lb	1000 ft, 2500 ft, 5000 ft
Ultra Filament Coated	7/16 in	5,000 lb	1000 ft, 2500 ft, 5000 ft
Ultra Filament Coated	1/2 in	5,500 lb	1000 ft, 2500 ft, 5000 ft

ULTRA™ WITH CORE

DIAMETER	APPROX. BREAK STRENGTH	STANDARD STOCK LENGTH
3/8 in	4,000 lb	1000 ft, 2500 ft, 5000 ft
7/16 in	6,100 lb	1000 ft, 2500 ft, 5000 ft
1/2 in	6,600 lb	1000 ft, 2500 ft, 5000 ft

